

B45196H, Tantalum, MnO2 Tantalum, 0.47 uF, 10%, 50 V, SMD, Molded, 3528, Height Max = 2.1mm



| General Information | |
|---------------------|--|
| Supplier: | KEMET |
| Series: | B45196H |
| Dielectric: | MnO2 Tantalum |
| Style: | SMD Chip |
| Description: | SMD, Molded |
| RoHS: | Yes |
| Termination: | Tin |
| Miscellaneous: | Closest Kemet Original Series Equivalent: T491B474K050AT |
| Notes: | Obsolete. Old Part Number [Obsolete] Was B45196H7474K209 |

| Dimensions | |
|------------|----------------|
| Footprint | 3528 |
| L | 3.5mm +/-0.2mm |
| W | 2.8mm +/-0.2mm |
| H | 1.9mm +/-0.2mm |
| S | 0.7mm +/-0.3mm |
| F | 2.2mm +/-0.1mm |
| K | 1.4mm TYP |

| Specifications | |
|------------------------|-------------------------------|
| Capacitance: | 0.47 uF |
| Capacitance Tolerance: | 10% |
| Voltage DC: | 50 VDC (85C), 33.5 VDC (125C) |
| Temperature Range: | -55/+125C |
| Rated Temperature: | 85C |
| Dissipation Factor: | 4% |
| Failure Rate: | N/A |
| Leakage Current: | 0.5 uA |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging: | T&R, 178mm |
| Packaging Quantity: | 2000 |