



JKL LAMP PART NO. (REFERENCE)	COLOR LCD HIGH OUTPUT WHITE 6700°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF26409-31B	x = 0.310 y = 0.321	1540	730	5 ± 1	36,000 ± 15%	20,000 MIN. 40,000 AVG.

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION				
	TITLE: MINIATURE COLD CATHODE FLUORESCENT LAMP					
DRAWN BY: L. WENGSTROM APPVD BY: LARRY R. DATE: 8/14/06	SIZE: A	FSCM NO.: 55335	DRAWING NO.: BF26409-31B			
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE: NONE	RELEASED DATE: 8/14/06	REVISION DATE:	REV. NO.:	SHEET 1 OF 1

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
	RELEASE AND CANCEL P-0606-05	8/14/06