

Technical specification:

Rated voltage: IEC 61076-2-101	4pos 250 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: DIN 40050-9	IP 69K, in mated condition
Temperature range: IEC 60664-1	-30°C ... +105°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PP GF, UL 94
Coupling screw:	1.4404 stainless steel
Moulding body:	Thermoplastic elastomer, grey

Installation specification:


Recommended torque:	0,6 Nm
---------------------	--------

Contact assignment:

- 1 ■ brown
- 2 ■ white
- 3 ■ blue
- 4 ■ black

Part no:	Description:	Length L:	Cable:
43-10520	SAL - FB - 12 - RS4 - 2 / P1	2m	PP, orange, 4x0,34mm ² Cable: 781-P13400
43-10521	SAL - FB - 12 - RS4 - 3 / P1	3m	
43-10522	SAL - FB - 12 - RS4 - 5 / P1	5m	
43-10523	SAL - FB - 12 - RS4 - 10 / P1	10m	
43-xxxxx	SAL - FB - 12 - RS4 - ... / P1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 21.02.11 VF Ä3909 technical specification changed, part no. cable in table added, data sheet modified	 dim. in mm	title:		
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%		date	name	Male connector M12x1 axial, FB
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	drawn	16.03.07	Mankopf	
		appd.	16.03.07	Fromm	43K1A061
				part no: see table	

